

Please type a plus sign (+) inside this box →



12-30-99

A

PTO/SB/05 (4/98)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket	02581- P0149A
First Inventor or Application Identifier	Simon SOLINGEN
Title	Medical Instrument, Particularly A Surgical
Express Mail Label No.	EM387358596US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

PTO
09/473502

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages **14 13**]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claims(s)
 - Abstract of the Disclosure
3. ☒ Drawings(s) (35 USC 113) [Total Sheets **2**]
4. Oath or Declaration [Total Pages **0**]
 - a. ☐ New executed (original or copy)
 - b. ☐ Copy from prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting
Inventors(s) named in the prior application,
see 37 CFR a.63(d)(2) and 1.33(b).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(where there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☒ Information Disclosure ☐ Copies of IDS
Statement (IDS)/PTO-1449 Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity ☐ Statement filed in prior application
Statement(s) Status still proper and desired
(PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other:

NOTE FOR ITEMS 1 & 4D: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 CFR § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 CFR § 1.28).

16. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information

☐ Continuation ☐ Divisional ☐ Continuation-in-part of prior application No.:

Prior application information: Examiner Group/Art Unit:

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

18. CORRESPONDENCE ADDRESS

☐ Customer Number of Bar Code Label (Insert Customer No or Attach bar code label here) or ☒ Correspondence address below

NAME	Wesley W. Whitmyer, Jr.				
ADDRESS	St. Onge Steward Johnston & Reens LLC				
	986 Bedford Street				
CITY	Stamford	STATE	CT	ZIP CODE	06905-5619
COUNTRY	United States	TELEPHONE	203 324-6155	FAX	203 327-1096

Name (Print/Type)	Wesley W. Whitmyer, Jr.	Registration No. (Attorney/Agent)	33,558
Signature		Date	12/28/99

Burden Hour Statement: This form is estimated to take 0.2 hour to complete. Times will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Office, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OF COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

PATENT
02581-P0149A WWW

UNITED STATES PATENT APPLICATION

of

Simon SOLINGEN
2927 Woodwardia Drive
Los Angeles, CA 90077


for

MEDICAL INSTRUMENT, PARTICULARLY A SURGICAL INSTRUMENT

Attorney for Applicant
Wesley W. Whitmyer, Jr., Registration No. 33,558
ST.ONGE STEWARD JOHNSTON & REENS LLC
986 Bedford Street
Stamford, CT 06905-5619
203 324-6155

Express Mail Certificate: I hereby certify that this correspondence is today being deposited with the U.S. Postal Service as *Express Mail Post Office to Addressee* Mailing Label Number EM387358596US in an envelope addressed to: BOX PATENT APPLICATION; Assistant Commissioner for Patents; Washington, DC 20231.

December 28, 1999


Morgen Dieringer

Our Ref 99 015 ST
Karl Storz GmbH & Co KG
Mittelstrasse 8
78532 Tuttlingen

A medical instrument, particularly a surgical instrument

The invention relates to a medical instrument, particularly a surgical instrument with a displaceable push/pull rod arranged on the proximal end of a hand manipulator for activating remote tool parts on the distal end, wherein a force-limiting device is envisaged for limiting the transmission of force from the hand manipulator onto the remote tool parts via the push/pull rod.

This kind of medical instrument can for example be a needle holder, a gripping-, holding- or preparation tool, scissors or other instrument, in which the push/pull rod can be moved back and forth using manual force via the hand manipulator, in order to move, ie to open and close, the remote tool parts which are predominantly open-ended tool parts.

These known medical instruments available in various embodiment configurations have a long hollow cylindrical shaft, onto the distal end of which the remote tool parts are arranged. The hand manipulator with a rigid handle element and a swivelling handle element is arranged on the proximal end of the shaft. To activate the remote tool parts via the hand manipulator, the remote tool parts and the swivelling handle element of the hand manipulator are coupled via the push/pull rod which is located in the hollow cylindrical shaft. In this way it is possible to open and close the remote tool parts by counter-adjusting

the handle elements of the hand manipulator with one another.

These types of medical instruments are often used during minimally invasive surgery where they are introduced into the patient's body using trocars. Due to the miniaturisation of the instruments required for minimally invasive surgery, the instruments are more sensitive to pressure since, due to miniaturisation, the individual components can only absorb marginal forces, which for example are brought about by hand pressure upon activating the hand manipulator. In the case of the type of medical instruments mentioned earlier, the swivel handle element of the hand manipulator is designed as a lever, wherein the hinge axis of the two handle elements form the lever axis. The distance from the hinge axis to the point at which the push/pull rod is located on the handle element is considerably shorter than the distance from the hinge axis to the finger hole on the end of this handle element. The transmission ratio is generally around 10:1, that is, the standard closing force of the hand of about 100 N is amplified tenfold due to mechanical leverage, i.e. to around 1,000 N.

When using these medical instruments in practice, in particular the gripping and holding tools, the aim is to generally hold an object, for example a swab or a needle and to place it securely and firmly between the remote tool parts. Strong people can exert a closing force onto the hand manipulator of about 150 N or more, which is then amplified to 1,500 N or more due to mechanical leverage. Frequent use of excess pressure on the remote tool parts can lead to material fatigue or even to the remote tool parts fracturing, whereupon loss of small parts in the operating arena particularly during an operation can lead to the patient getting injured.

In order to avoid undue excess forces being exerted onto the push/pull rod via the hand manipulator and therefore onto the remote tool parts, a force-limiting device is known in the practical field in which the transmission of force between the hand manipulator and the push/pull forces and/or the remote tool parts is limited by a force-limiting device. This type of force-limiting device is known for example from DE 197 31 453-C2. With this known device the push/pull rod is designed as a two-piece component, in which both the push/pull rod sections are connected to one another by way of a force-limiting device. One section of the rod is designed with a casing comprising an internal steepening flat body wedge across the direction of movement of the push/pull rod. The other rod section has a tapered cone with a corresponding flat body wedge, which is located inside the casing of the first rod section. The casing is designed with slots which are expanded by the displaceable tapered cone along the flat body wedge of the casing upon being subjected to tensile pressure of the push/pull rod, through which a portion of the closing force generated is absorbed, so that no further undue excess pressure can be exerted onto the remote tool parts.

In accordance with another known embodiment configuration the force-limiting device is designed as a spring assembly on the proximal end of the push/pull rod and which absorbs a portion of the force transmitted onto the push/pull rod via the hand manipulator.

All these state of the art known force-limiting devices have indeed proven themselves in practice, however their construction is very complicated and time consuming and therefore expensive.

Moving on from this the invention is based on the exercise of improving a medical instrument of the above mentioned

type so that the force-limiting device is simple and cost effective to construct.

The solution to this exercise according to the invention is characterised by the push/pull rod being designed with spring-like elasticity along the line of displacement and thus creating the force-limiting device.

By configuring the push/pull rod as a spring-like elastic component it is possible to produce a medical instrument with a force-limiting device without additional components for the first time.

In accordance with the first embodiment configuration the push/pull rod is designed with at least sectional undulatory curves to provide the spring-like elasticity. This configuration provides the opportunity for the push/pull rod to elongate itself, preferably reversibly, in the area of the undulatory curve in the event of being subjected to excess tensile pressure.

In order to avoid the push/pull rod from jumping from one side of the inner wall of the hollow cylindrical shaft to the other under tensile pressure, the invention furthermore suggests that the undulatory curves of the individual sections be designed offset on planes from one another, so that the push/pull rod can be guided through the inside of the hollow shaft tube in all directions. It suggests that the each of the sections with individual undulatory curves preferably be designed on planes, offset at 90° from one another. This embodiment configuration is simple to manufacture by placing the push/pull rod repeatedly into a press.

The invention further suggests an embodiment configuration in which the semi-curves of the undulatory curves creating

the undulating force-limiting device are offset at 90° or 135° from one another.

The spring-like elasticity of the push/pull rod can in one configuration of the invention be adjusted through its shape and the number of undulatory curves so that it is possible for the force-limiting device to be adapted to the respective necessary and appropriate closing pressure.

A second embodiment configuration of the invention suggests that the push/pull rod be designed with at least sectional turned spiral coils to provide the spring-like elasticity. Along with the creation of the undulatory curves, the spiral coil configuration of the push/pull rod offers the opportunity for the push/pull rod to flexibly elongate itself in the event of excess tensile pressure.

With this embodiment configuration the spring-like elasticity of the push/pull rod is preferably adjusted through the gradient of the turned spiral coil sections, in which the turned spiral coil sections preferably have a large gradient.

Finally the invention suggests that the spring-like elasticity of the push/pull rod can be adjusted by way of the material used for the push/pull rod.

Further, for technical and production reasons as well as for increasing operational safety, it is suggested that the push/pull rod be made of one uniform piece of material and/or with a virtually ~~[consistent]~~
constant cross section.

Further characteristics and advantages of the invention can be extracted from the following description of the associated diagram, in which the one embodiment configuration for creating a force-limiting device for a

medical instrument according to the invention is depicted.
The diagrams show:

Fig 1 a side view of a surgical instrument according to the invention in the form of a gripping tool

Fig 2a a side view of a force-limiting device of a medical instrument per Fig 1 with undulatory curved sections, and

Fig 2b a side view of the force-limiting device per Fig 2a, however rotated 90°.

Fig 1 depicts a surgical instrument in the form of a gripping tool 1. The gripping tool 1 has a hollow cylindrical shaft 2 along its lateral length, on the proximal end of which a hand manipulator 3 is located, and on the distal end of which remote tool parts 4 are arranged in the form of two open-ended sections and which can be activated via the hand manipulator 3 of the gripping tool 1.

The remote tool parts 4 are designed so that one remote tool part 4a is rigidly connected to the shaft 2, whilst the other remote tool part 4b is located and can swivel on an axis 5 across from the rigid remote tool part 4a. Understandably it is also possible for both remote tool parts 4 to be designed to swivel.

The hand manipulator 3 for activating the remote tool parts 4 has two handle elements 3a and 3b which swivel on hinge axes 6 across from the shaft 2.

The connection between the hand manipulator 3 - more precisely the swivelling handle elements 3a and 3b of the hand manipulator 3 - and the swivelling remote tool parts

4b of the remote tool part 4 is provided via a push/pull rod 7 located and guided inside the hollow cylindrical shaft 2.

If the gripping tool 1 is grabbed in the open position depicted in Fig 1, whereupon the handle elements 3a and 3b of the hand manipulator 3 are encompassed by the operator's hand, it is necessary, in order to guide the remote tool part 4 into grabbing position, to manipulate the swivelling handle elements 3a and 3b towards one another in the direction of arrow 8, through which action the push/pull rod 7 is proximally displaced in a line with the arrow 9, and which furthermore leads to the swivelling remote tool part 4b being displaced in the direction of the closed position.

Activation of the push/pull rod 7 via the handle elements 3a, 3b of the hand manipulator 3 is carried out via control levers 10 which, forming a parallelogram on the one hand, are located on the hand grips 3a, 3b and which swivel at the knuckle joints 11 and on the other hand are located at a pivot point 12 on the push/pull rod 7.

In order to determine on the one hand the position of the two handle elements 3a and 3b to one another and therefore the respective remote tool parts 4a and 4b, and on the other hand to independently guide the handle elements 3a and 3b into their open base position again according to Fig 1, the gripping tool 1 depicted has on the one hand a locking device 13, via which the handle elements 3a and 3b can be interlocked with one another, and which on the other hand has a spiral coiled spring 14 arranged on the proximal end of the push/pull rod 7. When the handle elements 3a, 3b are pressed together, the spiral coil spring 14 is elongated. The locking device 13 depicted for fixing the handle elements 3a, 3b comprises a draw rod 13a and a lock

clip 13b which are each connected to one handle element 3a, 3b facing one another.

As soon as the lock clip of the locking device 13 is lifted via a releasing mechanism 15, the spiral coil spring 14 recoils and pushes the handle elements 3a and 3b apart again into the base position by way of the two control levers 10, as depicted in Fig 1.

As can be seen in Fig 1 the distance from the outer end of the swivelling handle elements 3a, 3b to the knuckle joint 11 of the control levers 10 connected to the push/pull rod 7 is very much greater than the distance between the knuckle joints 11 and the pivot point 12 for the control levers 10 on the push/pull rod 7. In this way the force which is exerted by the hand onto the swivelling handle elements 3a, 3b is amplified due to mechanical leverage, wherein the normal transmission ratio is about 10:1. With a normal closing force of about 100 N the exerted force on the push/pull rod 7 is about 1,000 N after tenfold amplification.

However a hand can also exert considerably greater force than 150 N or more, therefore the gripping tool 1 depicted has a force-limiting device 16, which is depicted in more detail in Fig 2a and 2b. The force-limiting device 16 is there to prevent undue excess force being exerted onto the remote tool parts 4 via the push/pull rod 7 which can lead to damage or even fracturing of the remote tool parts 4.

In the diagrams in Fig 2a and Fig 2b a configuration of the force-limiting device 16 is depicted which totally eliminates additional components since, according to this embodiment configuration, the push/pull rod 7 simultaneously assumes the same function as the force-limiting device 16. To this end the push/pull rod 7 is designed to have spring-like elasticity along its line of

SECRET

displacement within the hollow cylindrical shaft 2, so that the push/pull rod 7 can be retracted and/or elongated with increasing tension in order to absorb excess forces and to block them from the reaching the remote tool parts.

In the embodiment configuration depicted with a spring-like elastic push/pull rod 7, the spring-like elasticity is achieved by designing the push/pull rod 7 with sectional undulatory curves along its total length. The opportunity exists for the push/pull rod 7 to flexibly distort in the area of the individual undulatory curves 17 and thereby partially transfer the force exerted onto the push/pull rod 7 into this distortion task.

In order to prevent the push/pull rod 7 from jumping from one side wall to the other side wall within the hollow cylindrical shaft 2 under tensile pressure when the undulatory curve 17 is designed on just one plane, the individual sections of the undulatory curves 17 are designed offset at 90° from one another respectively as depicted in Figs 2a and 2b.

With this embodiment configuration the spring-like elasticity of the push/pull rod 7 can be adapted and determined by way of the type and number of undulatory curves 17 as well as the choice of material for the push/pull rod 7.

Along with the embodiment configuration depicted, in which the undulatory curves 17 can be simply and advantageously manufactured, singly or multiply, by laying the straight push/pull rod 7 in a press, the spring-like elasticity of the push / pull rod 7 can also be achieved by the push/pull rod 7 at least being designed with sectional turned spiral coils. With this embodiment configuration (not illustrated) the spring-like elasticity of the push/pull rod 7 can be adapted through the choice of material for the push / pull

rod 7 as well as through the gradient of the turned spiral coils, wherein a greater gradient is seen as preferential.

The force-limiting device 16 depicted in Fig 2a and 2b is distinguished by being simple and cost effective to manufacture without additional components.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2

PATENT CLAIMS

1. A medical instrument, particularly a surgical instrument with a displaceable push/pull rod arranged on the proximal end of a hand manipulator for activating remote tool parts at the distal end, wherein a force-limiting device is envisaged for limiting the transmission of force onto the remote tool parts from the hand manipulator via the push/pull rod characterized in that for creating the force-limiting device the push/pull rod is designed to have spring-like elasticity along its lateral length.
2. A medical instrument according to Claim 1, characterized in that the push/pull rod has at least sectional undulatory curves to provide the spring-like elasticity.
3. A medical instrument according to Claim 2, characterized in that the individual sections with undulatory curves are designed on planes offset from one another.
4. A medical instrument according to Claim 3, characterized in that the individual sections with undulatory curves are each designed on planes offset at 90° from one another.
5. A medical instrument according to Claim 2, characterized in that the individual semi-curves of the sections with undulatory curves are designed to be offset at 90° or 135° from one another.
6. A medical instrument according to Claim 2, characterized in that the spring-like elasticity of the push/pull rod can be adjusted through its shape and/or the number of undulatory curves.

7. A medical instrument according to Claim 1, characterized in that the push/pull rod is designed with at least turned spring coil sections to provide the spring-like elasticity.
8. A medical instrument according to Claim 7, characterized in that the push/pull rod can be adjusted through the gradient of the turned spring coil sections.
9. A medical instrument according to Claim 7, characterized in that the turned spring coil sections have a large gradient.
10. A medical instrument according to Claim 1, characterized in that the spring-like elasticity of the push/pull rod can be adjusted via the material of the push/pull rod.
11. A medical instrument according to Claim 1, characterized in that the push/pull rod is made from one uniform piece of material.
12. A medical instrument according to Claim 1, characterized in that the push/pull rod has a virtually constant cross section.

ABSTRACT

The invention relates to a medical instrument, particularly a surgical instrument with a displaceable push/pull rod arranged on the proximal end of a hand manipulator for activating remote tool parts on the distal end, in which a force-limiting device is envisaged for limiting the transmission of force onto the remote tool parts from the hand manipulator via the push/pull rod. In order to design a simple and cost effective force-limiting device the push/pull rod is designed to be spring elastic in its lateral length.

145 1

Fig. 1

